

# powermaster

## RSG

**Slide Gate Operator for use in Residential, Commercial, Industrial and Restricted Access applications for gates up to 14' wide and 350 lbs.**

### STANDARD FEATURES

- PSC MOTOR
- SOLID STATE BOARD WITH CUSTOM PROGRAMMED MICRO PROCESSOR
- TIMER TO CLOSE
- MASTER/SLAVE OPERATION
- LEFT/RIGHT CHANGEVER IN FIELD
- NEMA 1 ONE-BUTTON CONTROL INCLUDED




*Complete selection of control stations  
& accessories are available.*

All gate operators must have contact and non-contact sensing system installed for operator to work properly and safely.

 [Facebook.com/PowerMasterOperators](https://www.facebook.com/PowerMasterOperators)

**www.PowerMasterNY.com**  
**SERVICING THE INDUSTRY SINCE 1969**



## SPECIFICATIONS & FEATURES

**AVAILABLE HORSE POWER:** 1/2 HP

**POWER OPTIONS:** 115V, 1 PHASE

CLASS II LOW VOLTAGE CONTROL CIRCUIT

**GATE CAPACITY:** 350 LBS, 14 FT WIDE, UP TO 10 CYCLES PER HOUR

**TRAVEL SPEED:** 12 INCHES PER SECOND

HEAVY DUTY #11 GA. STEEL FRAME

HARD SHELL, BAKED-ON, WEATHER RESISTANT POWDER COATING


V-BELT PRIMARY REDUCTION FOR SMOOTH, QUIET AND POSITIVE OPERATION

EASY PULL AND LATCH DRIVE DISCONNECT FOR MANUAL OPERATION IN CASE OF POWER FAILURE

POST OR PAD MOUNTABLE

UL 325 LISTED FOR USE IN CLASS I THROUGH IV APPLICATION

**SHIPPING WEIGHT:** APPROX. 90 LBS



## OPTIONAL EQUIPMENT

- RADIO CONTROL
- ADDITIONAL SAFETY EDGE (CONTACT SAFETY SENSOR)
- ADDITIONAL PHOTO CELL (NON-CONTACT SAFETY SENSOR)
- LOOP DETECTORS
- CARD KEY READER
- INTERIOR AND EXTERIOR CONTROL STATIONS
- THREE SECOND ADVANCE AUDIO WARNING SIGNAL AVAILABLE UPON REQUEST

## CAUTION

A moving gate can cause serious injury or death! Carefully read and follow all safety instructions, precautions, and guidelines when installing and using this product. Motorized gates are for vehicles only. Pedestrians must use a separate entrance. **NO ONE SHOULD CROSS THE PATH OF A MOVING GATE!** Proper reversing devices must be installed on gates to avoid all hazards, pinch points and entrapment. Eliminate all hazards, pinch points and entrapment areas. Warning signs must be permanently installed and visible to traffic and pedestrians. Do not mount operating devices accessible through gates or between a gate and wall. Never allow children to lay in the path of a gate. Never allow children to operate or play with the gate controls. Follow UL 325 and ASTM F220-02 standards. Do not install this product unless all hazards, pinch points and entrapment points are protected.

